

Small bar mounting point											Large bar mounting point									
327P4/327PSX	327PT55	436 Li/536 LiXP®	T336 LiXP®	317 Electric/321 Electric	T425	T435	338 XP®T/T540 XP®	135/135 e-series	339 XP®	435 e-series/435/440 e-series	445/445 e-series/450 e-series	545/550 XP®	455 Rancher/455 e-series Rancher	460 Rancher	555/560 XP®	562 XP®	365/372 XP®	570/576 XP®	390 XP®*/395 XP®	3120 XP®
LAMINATED BAR WITH NOSE WHEEL																				
Bar length inches / cm	Chain pitch inches	Gauge inches / cm	Product number	Drive links	Type	Product number														
10/25	3/8	.043/1.1	501 95 95-40	40	H38 LowVib	501 84 23-40														
12/30	3/8	.043/1.1	501 95 95-45	45	H38 LowVib	501 84 23-45														
14/35	3/8	.043/1.1	501 95 95-52	52	H38 LowVib	501 84 23-52														
10/25	3/8	.050/1.3	505 89 16-40	40	H37 LowVib	576 93 65-40														
12/30	3/8	.050/1.3	501 95 92-45	45	H37 LowVib	576 93 65-45														
14/35	3/8	.050/1.3	501 95 92-52	52	H37 LowVib	576 93 65-52														
16/40	3/8	.050/1.3	501 95 92-56	56	H37 LowVib	576 93 65-56														
13/33	.325	.050/1.3	508 92 61-56	56	H30 LowVib	501 84 06-56														
15/38	.325	.050/1.3	508 92 61-64	64	H30 LowVib	501 84 06-64														
16/40	.325	.050/1.3	508 92 61-66	66	H30 LowVib	501 84 06-66														
18/45	.325	.050/1.3	508 92 61-72	72	H30 LowVib	501 84 06-72														
20/50	.325	.050/1.3	508 92 61-80	80	H30 LowVib	501 84 06-80														
13/33	.325	.058/1.5	508 91 21-56	56	H25 LowVib	501 84 04-56														
15/38	.325	.058/1.5	508 91 21-64	64	H25 LowVib	501 84 04-64														
16/40	.325	.058/1.5	508 91 21-66	66	H25 LowVib	501 84 04-66														
18/45	.325	.058/1.5	508 91 21-72	72	H25 LowVib	501 84 04-72														
20/50	.325	.058/1.5	508 91 21-80	80	H25 LowVib	501 84 04-80														
15/38	3/8	.058/1.5	508 91 41-56	56	H42 LowVib	501 84 14-56														
16/40	3/8	.058/1.5	508 91 41-60	60	H42 LowVib	501 84 14-60														
18/45	3/8	.058/1.5	508 91 41-68	68	H42 LowVib	501 84 14-68														
20/50	3/8	.058/1.5	510 15 35-72	72	H42 LowVib	501 84 14-72														
15/38	3/8	.058/1.5	508 91 31-56	56	H42 LowVib	501 84 14-56														
16/40	3/8	.058/1.5	508 91 31-60	60	H42 LowVib	501 84 14-60														
18/45	3/8	.058/1.5	508 91 31-68	68	H42 LowVib	501 84 14-68														
20/50	3/8	.058/1.5	544 28 55-72	72	H42 LowVib	501 84 14-72														
LAMINATED BAR WITH NOSE WHEEL, TECHLITE™																				
12/30	3/8	.043/1.1	578 10 68-45	45	H38 LowVib	501 84 23-45														
14/35	3/8	.043/1.1	578 10 68-52	52	H38 LowVib	501 84 23-52														
12/30	3/8	.050/1.3	576 83 07-45	45	H37 LowVib	576 93 65-45														
14/35	3/8	.050/1.3	576 83 07-52	52	H37 LowVib	576 93 65-52														
16/40	3/8	.050/1.3	576 93 65-56	56	H37 LowVib	576 93 65-56														
LAMINATED BAR WITH REPLACEABLE TIP, TECHLITE™																				
20/50	3/8	.058/1.5	544 90 25-72	72	H42 LowVib	501 84 14-72														
28/70	3/8	.058/1.5	544 90 25-92	92	H42 LowVib	501 84 14-92														
SOLID BAR WITH REPLACEABLE TIP																				
18/45	3/8	.058/1.5	501 95 77-68	68	H42 LowVib	501 84 14-68														
20/50	3/8	.058/1.5	501 95 77-72	72	H42 LowVib	501 84 14-72														
18/45	3/8	.058/1.5	501 95 69-68	68	H42 LowVib	501 84 14-68														
20/50	3/8	.058/1.5	501 95 69-72	72	H42 LowVib	501 84 14-72														
24/60	3/8	.058/1.5	501 95 69-84	84	H42 LowVib	501 84 14-84														
28/70	3/8	.058/1.5	501 95 69-92	92	H42 LowVib	501 84 14-92														
SOLID BAR																				
10/25	1/4	.050/1.3	505 89 15-60	60	H00	501 84 40-60														
10/25	1/4	.050/1.3	575 84 22-58	58	H00	501 84 40-58														
12/30	1/4	.050/1.3	575 84 22-64	64	H00	501 84 40-64														
18/45	3/8	.058/1.5	501 95 80-68	68	H42 LowVib	501 84 14-68														
20/50	3/8	.058/1.5	501 95 80-72	72	H42 LowVib	501 84 14-72														
24/60	3/8	.058/1.5	501 95 80-84	84	H42 LowVib	501 84 14-84														
28/70	3/8	.058/1.5	501 95 80-92	92	H42 LowVib	501 84 14-92														
24/60	.404	.063/1.6	507 47 60-46	76	H64	501 84 31-76														
28/70	.404	.063/1.6	501 58 96-01	84	H64	501 84 31-84														
30/75	.404	.063/1.6	501 95 81-92	92	H64	501 84 31-92														
36/90	.404	.063/1.6	501 95 81-04	104	H64	501 84 31-04														
42/105	.404	.063/1.6	501 92 18-24	124	H64	501 84 31-24														

\*Solid bar with .404 chain pitch on 390 XP® is optional on certain markets.